



#### APPLICATIONS:

- Drill stem testing
- Tubing-conveyed perforating
- Stimulations
- Fracking
- Acidizing and injection operations
- Shallow wells

#### FEATURES:

- Retrievable
- Right hand set and release
- Can withstand tension, compression, or neutral loading
- Large internal bypass
- Pressure rating: 10,000 psi

The MI-X Casing Packer can be set with tubing in tension, compression or neutral. Equipped with a mechanical lock set action, the internal bypass can be set to the closed position before setting the packer, or while running in-hole/retrieving the packer. Seals below the upper slips allow debris above the packer to be displaced before the packer seat is released.

SPECIFICATIONS:

CASING SIZE (IN.)	CASING WEIGHT (LBS. LFT.)	CASING ID MIN (IN.)	CASING ID MAX (IN.)	TOOL OD MAX (IN.)	TOOL BORE MIN. (IN.)	THREAD SPEC. BOX UP/PIN DOWN (IN.)
<b>3 1/2</b>	7.70-10.20	2.797	2.867	2.786	1.254	1.900 NU 10RD
<b>4 1/2</b>	15.10-16.60	3.629	3.701	3.255	1.495	1.900 NU 10RD
“ ”	13.50-15.10	3.826	3.920	3.655	1.930	2-3/8 EU 8RD
“ ”	9.50-13.50	3.920	4.090	3.759	1.930	2-3/8 EU 8RD
<b>5</b>	20.80-21.40	4.126	4.156	3.943	1.930	2-3/8 EU 8RD
“ ”	18.00-20.80	4.156	4.276	4.000	1.930	2-3/8 EU 8RD
“ ”	11.50-15.00	4.408	4.560	4.125	1.930	2-3/8 EU 8RD
<b>5 1/2</b>	20.00-23.00	4.670	4.778	4.500	1.995	2-3/8 EU 8RD
“ ”	17.00-20.00	4.778	4.892	4.625	1.995	2-3/8 EU 8RD
“ ”	13.00-17.00	4.892	5.044	4.625	1.995	2-3/8 EU 8RD
“ ”	20.00-23.00	4.670	4.778	4.500	2.360	2-7/8 EU 8RD
“ ”	15.50-17.00	4.778	4.950	4.625	2.360	2-7/8 EU 8RD
“ ”	13.00-15.50	4.950	5.044	4.781	2.360	2-7/8 EU 8RD
<b>7</b>	32.00-38.00	5.920	6.094	2.515	2.515	2-7/8 EU 8RD
“ ”	26.00-32.00	6.094	6.276	5.875	2.515	2-7/8 EU 8RD
“ ”	20.00-26.00	6.276	6.538	6.000	2.515	2-7/8 EU 8RD
“ ”	17.00-20.00	6.456	6.538	6.255	2.515	2-7/8 EU 8RD
“ ”	32.00-38.00	5.920	6.094	5.750	2.990	3-1/2 EU 8RD
“ ”	26.00-32.00	6.094	6.276	5.875	2.990	3-1/2 EU 8RD
“ ”	17.00-24.00	6.336	6.538	6.000	2.990	3-1/2 EU 8RD
<b>7 5/8</b>	33.70-39.00	6.625	6.765	6.453	2.515	2-7/8 EU 8RD
“ ”	24.00-29.70	6.875	7.025	6.672	2.515	2-7/8 EU 8RD
“ ”	33.70-39.00	6.625	6.765	6.453	2.990	3-1/2 EU 8RD
“ ”	24.00-29.70	6.875	7.025	6.672	2.990	3-1/2 EU 8RD
<b>9 5/8</b>	43.50-53.50	8.535	8.755	8.250	2.990	4-1/2 EU 8RD
“ ”	32.00-43.50	8.755	9.001	8.500	2.990	4-1/2 EU 8RD

\* Note: The most common sizes and specifications are depicted above. Other sizes are available upon request

\* Premium Connections Available