



APPLICATIONS:

- Drill stem testing
- Tubing-conveyed perforating
- Stimulations
- Fracking
- Acidizing and injection operations

FEATURES:

- J-slot right hand rotation to set
- Straight pull to release
- Hydraulic hold down slips engage during injection operations
- Large bypass for circulating
- Pressure rating: 6,000 psi - 10,000 psi

The R-Type Casing Packer is set by: picking up, rotating to the left or right (depending on the “J” configuration), and setting down. Pressure below the packer forces the hydraulic hold-down-buttons to engage against the casing, preventing the packer from being pumped up the well bore. Upward pull on the tubing will open the bypass and unset the packer.

SPECIFICATIONS:

CASING SIZE (IN.)	CASING WEIGHT (LBS. LFT.)	CASING ID MIN (IN.)	CASING ID MAX (IN.)	TOOL OD MAX (IN.)	THREAD SPEC. BOX UP/PIN DOWN (IN.)
4.5	9.50-13.50	3.920	4.090	3.770	2 - 3/8 EU 8RD
5.0	15.00-18.00	4.276	4.408	4.110	2 - 3/8 EU 8RD
5.5	20.00-23.00	4.670	4.778	4.500	2 - 3/8 EU 8RD
“ ”	15.50-20.00	4.778	4.950	4.641	2 - 3/8 EU 8RD
“ ”	13.00-15.50	4.950	5.044	4.781	2 - 3/8 EU 8RD
5 3/4	18.00-21.90	5.039	5.354	4.817	2 - 3/8 EU 8RD
6	20.00-23.00	5.191	5.390	5.062	2 - 3/8 EU 8RD
“ ”	15.00-18.00	5.391	5.560	5.156	2 - 3/8 EU 8RD
6 5/8	24.00-28.00	5.791	5.920	5.588	2-7/8 EU 8RD or 3-1/2 IF
7	32.00-35.00	6.004	6.94	5.812	2-7/8 EU 8RD or 3-1/2 IF
“ ”	26.00-29.00	6.184	6.276	5.968	2-7/8 EU 8RD or 3-1/2 IF
“ ”	20.00-26.00	6.276	6.456	6.078	2-7/8 EU 8RD or 3-1/2 IF
7 5/8	33.70-39.00	6.625	6.765	6.458	2-7/8 EU 8RD or 3-1/2 IF
“ ”	26.40-33.70	6.765	6.969	6.593	2-7/8 EU 8RD or 3-1/2 IF
“ ”	24.00-29.70	6.875	7.025	6.672	2-7/8 EU 8RD or 3-1/2 IF
9 5/8	47.00-53.50	8.535	8.681	8.218	3-1/2 EU 8RD or 3-1/2 IF
“ ”	40.00-47.00	8.681	8.835	8.437	3-1/2 EU 8RD or 3-1/2 IF
10 3/4	65.70-81.00	9.250	9.560	9.000	3-1/2 EU 8RD or 3-1/2 IF
“ ”	55.50-60.70	9.660	9.760	9.376	3-1/2 EU 8RD or 3-1/2 IF
“ ”	32.75-51.00	9.850	10.192	9.625	3-1/2 EU 8RD or 3-1/2 IF
11 3/4	60.00-83.00	10.368	10.772	10.06	4 - 1/2 IF
“ ”	42.00-65.00	10.682	11.084	10.38	4 - 1/2 IF
13 3/8	48.00-72.00	12.347	12.715	12.13	4 - 1/2 IF

* Note: The most common sizes and specifications are depicted above. Other sizes are available upon request

* Premium Connections Available